



STAMP WITH VOLTAGE,
CONTACT FORM AND
DELAY TIME

TMC CODE	VOLTAGES AVAILABLE
6	6.3
26	26
115	115

TIME DELAYS AVAILABLE IN SEC.	
5	30
10	45
15	60
20	75
	90

REQ. PER UNIT	USED ON			RL166	A
	MODEL	ASS'Y. NO.	DATE		
1	RTTD-1	A3704	10-14-64		

CONTACTS: SPST NORMALLY OPEN
OR NORMALLY CLOSED.
RATED AT 2 AMPS, 115 V. AC.
HEATER VOLTAGE: SEE CHART
HEATER POWER: 2 1/2 WATTS NOMINAL
TIME DELAY: SEE CHART
TOLERANCE OF TIME DELAY: ±20 %
WEIGHT: LESS THAN 1/2 OZ.
FINISH: ALUMINUM

TMC PART NO. TO BE IN THE FOLLOWING FORM:

RL166-6-NO-90

BASIC PART NUMBER

VOLTAGE CODE

CONTACTS	
NC	NORMALLY CLOSED
NO	NORMALLY OPEN

DELAY TIME IN SEC.
90

STANDARD DRAWING

SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.	REQ. ITEM	PART NO.	EATON	DESCRIPTION	SYMBOL		
A	"STAMP" NOTE REVISED	11-7-66	upw	17192									
Ø	ORIGINAL RELEASE FOR PRODUCTION	11-30-64	Ø	ØL									
X1	BASIC P/N & (2) CHARTS ADDED	11-24-64	X1										
X	EXPER. RELEASE	10-14-64	X										
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES							SCALE						
							1:1						
DECIMALS .X ± .05 .XX ± .01 .XXX ± .005							FRACTIONS ± 1/64 ANGLES ± 0° 30'		CODE		C	5401-316	
							TYPE & TEMPER		HEAT TREAT. SPEC.		DRAWN	CHECKED	FINAL APPROVAL
											G. Jensen	11-24-64	RJC
							FINISH & SPEC. NO.		ELEC. DES. APP.		MECH. DES. APP.	RL166	A