

APPLICATION

QTY	MODEL USED ON	ASS'Y NO.	LTR	DESCRIPTION	DATE	E.M.N.NO	DRAFT	CHKD	APPD
1	BCT 10KA	AX681	X	EXPERIMENTAL RELEASE	8/24/67	X	C.V.		
			Ø	ORIG RELEASE FOR PROD.	8/28/67	Ø	C.V.		
			A	DELE NOTE	3/20/71	20306	GE		

REVISIONS

TMC P/N	MFGR P/N	COIL VOLTAGE	COIL FREQ.	* AUX. CONTACTS
RL179-1	DE1615	230 VAC	60 HZ	NO

* AUX. CONTACTS: 2 SPDT
ELECTRICAL RATING: 10 AMPS @125/250 VAC

VACUUM SWITCH ELECTRICAL SPECIFICATIONS

SWITCH KV PK TEST: 15 KV @60 CY
SWITCH RATING: 100 AMPS

DIMENSION TOLERANCES WILL BE AS DESCRIBED IN MANUFACTURES LITERATURE.

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
AND INCLUDE CHEMICALLY APPLIED
OR PLATED FINISHES.

DECIMALS FRACTIONS
.X ± .05 TOLS. 1/64
.XX ± .01 ANGLES 0° .30'
.XXX ± .005

MATERIAL

FINISH

S401-48

REQ'D ITEM PART NUMBER DESCRIPTION SYM.

F. BUDETTI

LIST OF MATERIAL

THE TECHNICAL MATERIEL CORP.

MAMARONECK, NEW YORK

SWITCH, VACUUM, SOLENOID, OPERATED

NOTICE TO PERSONS RECEIVING THIS DRAWING
THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.

SIZE CODE IDENT. NO. DWG NO.

A 82679

RL 179

ISSUE

A

SCALE

M/L *WFA*

SHEET

OF