

APPLICATION			REVISIONS							
QTY	MODEL USED ON	ASS'Y NO.	LTR	DESCRIPTION	DATE	E.M.N.NO	DRAFT	CHKD	APPD	
1	BCT 10KA	AX681	X	EXPERIMENTAL RELEASE	8/24/67	X	C.V.			
			Ø	ORIG RELEASE FOR PROD.	8/28/67	Ø	C.V.			
			A	DELE NOTE	3/30/71	20306	GE			

TMC P/N	MFGR P/N	COIL VOLTAGE	COIL FREQ.	* AUX. CONTACTS
RL179-1	DE1615	208 VAC*	400 Hz	NO

* AUX. CONTACTS: 2 SPDT
 ELECTRICAL RATING: 10 AMPS @125/250 VAC

VACUUM SWITCH ELECTRICAL SPECIFICATIONS
 SWITCH KV PK TEST: 15 KV @400 CY
 SWITCH RATING: 100 AMPS

NOT USED

DIMENSION TOLERANCES WILL BE AS DESCRIBED IN MANUFACTURES LITERATURE.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		REQ'D	ITEM	PART NUMBER	DESCRIPTION	SYM.
DECIMALS X ± .05 .XX ± .01 XXX ± .005	FRACTIONS 1/64 ANGLES 0° 30'	F. BUDETTI LIST OF MATERIAL				
MATERIAL	FINAL APPROVAL	THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK				
FINISH	MECH. DES.	SWITCH, VACUUM, SOLENOID, OPERATED				
S401-48	ELECT. DES.					
	CHECKED					
	DRAWN					

NOTICE TO PERSONS RECEIVING THIS DRAWING
 THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.

SIZE A	CODE IDENT. NO. 82679	DWG NO. RL 199	ISSUE
SCALE	M/L W/F	SHEET	OF