

| | | | | | |
|-------------|--------|------------|------|-------|---|
| RE PER UNIT | MODEL | USED ON | DATE | S 603 | Ø |
| | GPR-92 | ASSTY. NO. | | | |

TEST PROCEDURE FOR A 2120

OBsolete

REPLACED BY _____

CRYSTAL FILTER ASSEMBLY TEST DATA

| | | | |
|-----------|--------------------|--|----------------|
| REQ. ITEM | PART NO. | DESCRIPTION | SYMBOL |
| | | THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK | |
| | STOCK SIZE | TEST PROCEDURE FOR | |
| | MATERIAL | A 2120 | |
| | TYPE & TEMPER | DRAWN | CHECKED |
| | HEAT TREAT SPEC. | | FINAL APPROVAL |
| | FINISH & SPEC. NO. | ELEC. DES. APP. MECH. DES. APP. | S 603 |
| | | | Ø |

| | | | | | | |
|---|-------|---------|---------|--------|---------|-----------|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES | SCALE | DATE | CH. NO. | DRAFTS | CHECKER | ENG. APP. |
| Ø ORIGINAL RELEASE FOR PRODUCTION DESCRIPTION | | 7/21/66 | Ø | CV | | |

| | | | |
|---|------------|---|------|
| DECIMALS X ± .05 .XX ± .01 .XXX ± .005 | TOLERANCES | FRACTIONS ± 1/64 ANGLES / ± 0° 30' | CODE |
|---|------------|---|------|