

DATE 10/24/63

SHEET 1 OF 6

TMC SPECIFICATION NO. S 785

0

RK
COMPILED

*Ray K...
28 10/24/63
CHECKED*

TITLE: PRODUCTION TEST PROCEDURE FOR TMC MODEL AX-413

APPROVED *RK*

POWER SUPPLY

PRODUCTION TEST PROCEDURE FOR TMC MODEL AX-413 POWER SUPPLY

DATE 10/24/63

SHEET 2 OF 6

TMC SPECIFICATION NO. S 785

0

RK
COMPILEDRon KOHN
28 OCT. 63
CHECKED ✓

TITLE: PRODUCTION TEST PROCEDURE FOR TMC MODEL AX-413

APPROVED

POWER SUPPLY

I INTRODUCTION

The AX-413 power supply is used with TMC model TTR-10 rec iver-transmitter when the TTR-10 is to be operated from an AC power source. The AX-413 is designed to operate from nominal AC line voltages of 115, 208 or 230 volts, single phase, 50 thru 400 cycles per second. The AX-413 provides all the A, B+, B-, C- and internal oven voltage for the TTR-10 unit. The power supply is installed in the TTR-10 by sliding it into the main chassis from the rear and is secured with six screws. Detailed descriptions of the TTR-10 systems, including the AX-413, are contained in TMC specification S-786. This specification includes theory of operation and trouble shooting data and should be referred to in the event of malfunction during test. The check sheet should be filled out during test.

II EQUIPMENT REQUIRED

1. Schematic Diagrams CK-659, sketch (4) E-3037-101.
2. Power Supply Test Jig. (TMC)
3. Simpson 260 multi-meter or equivalent.
4. Metered Variac model W10MT3W, or equivalent.
5. Line cord, TMC CA-555-4.
6. Ballantine AC VTVM model 314, or equivalent.

III PROCEDUREA. Nominal Voltage Check.

1. Check the AX-413 for mechanical defects and wiring errors.
2. Check that all fuses are installed and are of the specified value.
3. Set all the toggle switches on the TEST JIG to the OFF position.
4. Set the OVEN VOLTAGE switch on the AX-413 to the center, OFF position.
5. Set the AX-413 on the bench upside down so that the circuitry is exposed.
6. Plug the TEST JIG into the AX-413 at J903.
7. Plug the Variac into the AC line and adjust the Variac output voltage to 115 volts.
8. Set the RANGE switch on the Variac to LOW and the LINE switch to OFF.
9. Connect the line cord between J900 on the AX-413 and the VARIAC output.
10. Set the LINE switch on the VARIAC to ON.

NOTE: READINGS NOTED AS "APPROXIMATELY" ARE ± 10%.

DATE 10/24/63

SHEET 3 OF 6

TMC SPECIFICATION NO. S 785

RK
COMPILEDDON KOHN
28 OCT. '63
CHECKED

TITLE:

PRODUCTION TEST PROCEDURE FOR TMC MODEL AX-413

APPROVED

POWER SUPPLY

11. Set the OVEN VOLTAGE switch on the AX-413 to the INT. position. The OVEN indicator on the TEST JIG should light.
12. Set S1 on the TEST JIG to ON. The POWER indicator should light and the VARIAC should read approximately 20 watts on its power meter.
13. Connect the Simpson 260 between the LV+ test jack and ground. The meter should read 12.5 volts DC + 5%. Leave meter connected.
14. Set S-6 on the TEST JIG to the ON position. The meter reading should not vary more than 1 volt. Remove meter.
15. Connect the meter between the MV- test jack and ground. The meter should read -36 volts DC + 10%. Leave meter connected.
16. Set S8 on the TEST JIG to the ON position. The meter reading should not vary more than 1 volt. Remove meter.
17. Connect the meter between the LV- test jack and ground. The meter should read -12.5 volts DC + 5%. Leave meter connected.
18. Set S-7 on the TEST JIG to the ON position. The meter reading should not vary more than 1 volt. Remove meter.
19. Check the VARIAC power reading, it should be approximately 55 watts.
20. Set S-3 on the TEST JIG to ON. The FIL, C-, and ANT. RELAY indicators should light. The VARIAC power should read approximately 100 watts.
21. Set S-2 on the TEST JIG to the ON position. The antenna relay within the AX-413 should energize and the ANT. RELAY indicator on the TEST JIG should go out.
22. Set the Simpson 260 to read AC VOLTS on the 10 volt scale and connect between the two FIL. test jacks. The meter should read 6.3 volts, minimum. Remove meter.
23. Set the Simpson to read -DC VOLTS on the 250 volt scale and connect the meter between the C- test jack and ground. The meter should read 105 + 5% volts. Remove meter.
24. Connect the meter between the PA BIAS test jack and ground. Varying the PA BIAS ADJ. knob should vary the meter reading between -25 and -80 volts. Remove meter.
25. Set the meter to read +DC VOLTS on the 10 volt scale and connect between the HV test jack and ground. The meter should read 9 volts + .2 volts.
26. Set the meter to the 1000 volt scale and connect to the IPA B+ test jack. The meter should read 400 volts + 20 volts. Leave meter.
27. Set S-4 on the Test Jig to ON. The meter reading should drop to 290 + 20 volts. Remove meter.
28. Connect the meter between the PAG₂ test jack and ground. The meter should read 315 volts + 5%. Leave meter connected.
29. Set S-5 on the Test Jig to ON. The meter reading should not vary more than 5 volts. The VARIAC power reading at this time should be approximately 135 watts. Leave meter connected.

DATE 10/24/63

SHEET 4 OF 6

TMC SPECIFICATION NO. S 785

0

RK
COMPILED

RON KOHN
28 OCT. '63
CHECKED

TITLE: PRODUCTION TEST PROCEDURE FOR TMC MODEL AX-413

APPROVED

POWER SUPPLY

III cont'd

B. Voltage Regulation Check

1. Vary the AC LINE VOLTAGE as measured on the VARIAC between 105 and 125 volts. The meter reading should not vary more than 15 volts. Remove meter and set line voltage at 115.
2. Set meter to read -DC volts on the 250 volt scale and connect between C- test jack and ground.
3. Vary the line voltage between 105 and 125 volts. The meter reading should not change more than 2 volts. Remove meter, set line voltage at 115.
4. Set the meter to the 50 volt scale and connect between the LV- test jack and ground.
5. Vary the line voltage between 105 and 125 volts. The meter reading should not vary more than .5 volt. Remove meter and set line voltage to 115.
6. Set the meter to read +DC volts and connect between the LV+ test jack and ground.
7. Vary the line voltage between 105 and 125 volts. The meter reading should not vary more than .5 volt. Remove meter and set the line voltage at 115.
8. Connect the meter between the MV+ test jack and ground.
9. Vary the line voltage between 105 and 125 volts. The meter reading should not vary more than 1 volt. Remove meter and set the line voltage at 115 volts.

III

C. Ripple Voltage Check

1. With the line voltage at 115 volts, connect the BALLANTINE AC VTVM between the MV+ test jack and ground. The meter should read less than 7.5MV RMS ripple. Remove meter.
2. Connect the BALLANTINE between the LV- test jack and ground. The meter should read less than 1MV. Remove meter.
3. Connect the BALLANTINE between the LV+ test jack and ground. The meter should read less than 1 MV. Remove meter.
4. Connect the BALLANTINE between the PAG₂ test jack and ground. The meter should read less than 40 MV. Remove meter.
5. Connect the BALLANTINE between the IPA B+ test jack and ground. The meter should read less than 300MV. Remove meter.
6. Connect the BALLANTINE between the HV test jack and ground. The meter should read less than 20MV. Remove meter.
7. Connect the BALLANTINE between the C- test jack and ground. The meter should read less than 3MV. Remove meter.

DATE 10/24/63

SHEET 5 OF 6

TMC SPECIFICATION NO. S 785

0

RK
COMPILED

RON KOHN
28 OCT. '63
CHECKED

TITLE: PRODUCTION TEST PROCEDURE FOR TMC MODEL AX-413

APPROVED

POWER SUPPLY

III

D. Shut-Down

1. Set S-2 on TEST JIG to OFF. The ANT. RELAY indicator should light.
2. Set S-1 on TEST JIG to OFF. All the indicators should go out except the OVEN indicator, and the power indicated on the VARIAC should reduce to 15watts.
3. Disconnect the line cord from J900 on the AX-413 and connect to J901. The OVEN indicator on the TEST JIG should go out.
4. Set the OVEN VOLTAGE switch on the AX-413 to the EXT. position. The OVEN indicator on the TEST JIG should light.
5. Set the OVEN voltage switch on the AX-413 to OFF. The OVEN indicator on the TEST JIG should go out.
6. Remove the TEST JIG and line cord. This completes testing of the AX-413 power supply.

1. MECHANICAL ASSEMBLY CHECK. _____ OK
2. WIRING CHECK. _____ OK
3. FUSE INSTALLATION CHECK. _____ OK
4. ELECTRICAL OPERATIONAL CHECK _____
 - a: INTERNAL OVEN VOLTAGE _____ OK
 - b: POWER LIGHT _____ OK
 - c: EXTERNAL OVEN VOLTAGE _____ OK
 - d: OUTPUT VOLTAGES (SEE CHART BELOW)

| REVISIONS | | | | | | |
|-----------|------------------|------|------------|-------|------|------|
| SYM | DESCRIPTION | DATE | E.M.N. NO. | DRAFT | CHKD | APPD |
| S-785 | SERIAL NO. _____ | | | | | |
| | MFG. NO. _____ | | | | | |

| TESTS AND REFERENCE SECTIONS | | | | | | | | | | | | | |
|------------------------------|------------------|-------------------|-----------------------------|----------|-------------------|--|----------|-------------------|--|----------|-------------------|---------------------------------|----------|
| POWER SUPPLY OUTPUT | TEST JIG JACK | REFERENCE SECTION | MINIMUM LOAD OUTPUT VOLTAGE | | REFERENCE SECTION | VOLTAGE VARIATION NO LOAD TO FULL LOAD | | REFERENCE SECTION | VOLTAGE VARIATION W/AC LINE AT FULL LOAD | | REFERENCE SECTION | RMS RIPPLE VOLTAGE AT TEST LOAD | |
| | | | NOMINAL | MEASURED | | MAXIMUM | MEASURED | | MAXIMUM | MEASURED | | MAXIMUM | MEASURED |
| LOW VOLTAGE B+, REG. | LV B+ | III:A:13 | +12.5±5% | | III:A:14 | 1.0 | | III:B:6,7 | 0.5 | | III:C:3 | 1.0 MV | |
| MID VOLTAGE B+, REG. | MV B+ | III:A:15 | +36±10% | | III:A:16 | 1.0 | | III:B:8,9 | 1.0 | | III:C:1 | 7.5 MV | |
| LOW VOLTAGE B-, REG. | LV B- | III:A:17 | -12.5±5% | | III:A:18 | 1.0 | | III:B:4,5 | 0.5 | | III:C:2 | 1.0 MV | |
| IPA & PA FILAMENT | FIL. | III:A:22 | 6.3 MIN | | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| PA BLOCKING BIAS, REG. | C- | III:A:23 | -105±5% | | N/A | N/A | N/A | III:B:2,3 | 2.0 | | III:C:7 | 3.0 MV | |
| PA Ib ADJ. (PA BIAS) | PA BIAS | III:A:24 | -25 THRU -80 | | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| IPA PLATE & SCREEN B+ | IPA B+ | III:A:26 | 400±20 | | III:A:27 | 120 | | N/A | N/A | N/A | III:C:5 | 300 MV | |
| PA PLATE VOLTAGE (Vx100) | HV | III:A:25 | +8.0±2 | | N/A | N/A | N/A | N/A | N/A | N/A | III:C:6 | 20 MV | |
| PA SCREEN VOLTAGE, REG. | PAG ₂ | III:A:28 | 315±5% | | III:A:29 | 5.0 | | III:B:1 | 15.0 | | III:C:4 | 40 MV | |

NOTE: N/A DENOTES NON-APPLICABLE

DATE: _____
 TESTED BY: _____

| REQ'D. | ITEM | PART NUMBER | DESCRIPTION | SYMB L |
|---|------|---|------------------|---------------------|
| LIST OF MATERIAL | | | | |
| MATERIAL | | THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK | | |
| FINISH | | TEST DATA SHEET, AK-413 | | |
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES | | DRAWN <i>R. Chivast</i> | DATE 10-25-63 | FINAL APPROVAL |
| | | CHECKED <i>V. Petros</i> | DATE 10-31-63 | |
| | | ELECT. DES. RKOHN | DATE 10-28-63 | S-785 |
| | | MECH. DES. — | DATE — | SHEET 6 OF 6 |
| DECIMALS .X ± .05 .XX ± .01 .XXX ± .005 | | FRACTIONS ± 1/64 ANGLES ± 0° 30' | | REV. LTR. |

| TY./UNIT | MODEL USED ON | ASBY. NO. |
|---|---------------|-----------|
| SCALE | CODE | |
| THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN. | | |

NOTES