

REQ. PER UNIT	USED ON		
	MODEL	ASS'Y. NO.	DATE
1	LRCB-1		4-1-65
1	LRCD-1		4-1-65


TF5026 \emptyset

— SPECIFICATIONS —

NO. OF TERMINALS : 2
 HI-POT : 1000
 DC RESIST. : .12
 INDUCTANCE : .03 HY. MIN. WITH 10 V. AC, 60 CPS,
 1.0 A. DC ON TERMINALS 1, 2.
 SPECIAL TESTS : .004 HY. MIN. WITH 10 V. AC, 60 CPS,
 6 A. DC ON TERMINALS 1, 2.

STKG. : BUTT
 GAP : .008
 HERM. SEALED
 POTTING MAT'L. : PITCH
 FINISH : GRAY
 STAMPING : MARKING PROCESS AS PER TMC
 SPEC. S-727. LETTERING TO BE
 BLACK GOTHIC LOCATED AS PER
 NOTE BELOW.

THE TECHNICAL MATERIEL CORP.
 MAMARONECK NEW YORK



.030 HY 1 A. DC
 .004 HY. 6 A. DC

NOTE :
 TO BE MARKED
 ON TOP OF FILTER

SCHEMATIC DIAGRAM

							REQ. ITEM	PART NO.	EATON	DESCRIPTION	SYMBOL	
							STOCK SIZE		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK			
							MATERIAL		CHOKE, FILTER			
\emptyset	ORIGINAL RELEASE FOR PRODUCTION	4-6-65	M	HCA			H. AUSTIN		<i>JKB</i>	<i>F. E. Eaton</i>		
SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.	TYPE & TEMPER		HEAT TREAT. SPEC.	DRAWN	CHECKED	FINAL APPROVAL
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES							SCALE					
DECIMALS .X \pm .05 .XX \pm .01 .XXX \pm .005		FRACTIONS \pm 1/64 ANGLES \pm 0° 30'		CODE C	5401-30 (6832)		FINISH & SPEC. NO.		ELEC. DES. APP.	MECH. DES. APP.	TF5026	\emptyset