

REQ. PER UNIT	USED ON			TT280	Ø
	MODEL	ASS'Y. NO.	DATE		
1	CDN-3	A 4351	2/11/66		


**ELECTRICAL SPECS.
(WITH SLUG INSERTED)**

OPERATING FREQUENCY: 455 KHZ
 INDUCTANCE @ 2.5 MHZ
 PRIMARY: 38 UH + & - 5 UH
 SECONDARY: NOT RATED
 "Q" (PRIMARY) @ 455 KHZ: > 65

MECHANICAL SPEC.

TURNS
 PRIMARY: 53 TAPPED AT 3
 SECONDARY:
 COLOR CODE: GRAY
 CASE: COPPER CAN
 CASE FINISH: TIN-PLATED
 QUANTITY TERM: 4
 MATERIAL:
 CORE & SLUG: POWERED IRON

SCHEMATIC



Ø	ORIGINAL RELEASE FOR PRODUCTION	2-16-66	Ø	ABS		JL
SYM.	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	SCALE				
	DECIMALS .X ± .05 .XX ± .01 .XXX ± .005	FRACTIONS ± 1/64 ANGLES ± 0° 30'	CODE A	2A4420		

REQ. ITEM	PART NO.	POSE	DESCRIPTION	SYMBOL
—//—	—//—		THE TECHNICAL MATERIEL CORP. MAMARONECK. NEW YORK	
	STOCK SIZE		TRANSFORMER, RF, ADJUSTABLE	
	—//—			
	MATERIAL			
—//—	—//—	J.L.	<i>[Signature]</i>	<i>[Signature]</i>
TYPE & TEMPER	HEAT TREAT. SPEC.	DRAWN	CHECKED	FINAL APPROVAL
—//—	—//—	<i>[Signature]</i>		
FINISH & SPEC. NO.	ELEC. DES. APP.	MECH. DES. APP.	TT280	Ø