
	REQ.				
Ì	PER. UNIT	MODEL	ASSY. NO.	DATE	UG-212C/U
				1-25-61	



SPECIFICATIONS

DIELECTRIC: TEFLON

GASKET: SILICONE

WEATHER PROOF: YES

NOMINAL IMEDANCE: CONSTANT FOR 50 A

O.K. FOR 701 WHEN NOT CRITICAL.

DESCRIPTION: HI VOLTAGE TYPE COUPLING

RING SCREW TYPE.

MAX. VOLTAGE: PEAK OF 4000 V @ 50,000 FEET

GOOD TO 5000V W/MODIFICATION.

PRACTICAL FREQ. LIMIT: GOOD TO 3000 Mc/SEC.

								REQ.	ITEM	P	ART NO.		DESCRIPTION	ON SYMBO
										STOCK S	SIZE	THE	MATERIEL CORP. NEW YORK	
				ļ								CONNEC.	TOR, RIGH	T ANGLE ADAPTE
				 			 	 		MATER	AL			SERIES
ISSUE	ITEM	CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.					D.J. Marin	1 1/4 /2	
TOLERANCES DEC. DIM. ± FRAC. DIM. ± ANGULAR DIM. ±			SCALE:								<u> </u>	CHECKED	FINAL APPROVAL	
			BEEN	MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION.				ТҮРІ	ERTEM	PEK INT	EATTREAT. SPEC.	DRAWN		UG-212C/U
			REMOVE ALL BURRS AND SHARP EDGES					FINISH & SPEC. NO.		ELEC. DES. APPMECH. DES. APP				