

SALES SERVICE BULLETIN NUMBER 244 A



Controlled Precision Oscillator, Model CPS-1



The TMC Model CPS-1, Controlled Precision Oscillator, is a synthesizer controlled master oscillator with a stability of 1 part in 10^8 per day and a "fail safe" feature of 20 parts per million. The unit covers the frequency range of 2 to 4 megacycles and is continuously tuneable throughout the range in 100 cycle increments.

All frequency determining elements in the CPS-1 are derived from a 1 megacycle source to provide the stability of 1 part in 10⁸. A phase detector circuit with direct meter indication allows this built-in standard to be compared to and corrected to a master or station standard. Also, the unit may be connected to an external standard of greater stability without degeneration of that standard.

The Model CPS-1 is housed in an attractive relay rack enclosure. The control portion of the unit occupies only 16-1/2 inches of rack space and all other components may be mounted seperately if this makes for a more convenient installation package.

TECHNICAL SPECIFICATIONS:

FREQUENCY RANGE:

2 to 4 megacycles in 100 cycle steps

FREQUENCY CONTROL:

All frequency determining elements referenced to

a built-in 1 mc standard.

FREQUENCY STABILITY:

1 part in 108 per day under normal fixed station

operating conditions.

OUTPUT POWER:

Continuously adjustable from zero to 1 watt.

OUTPUT IMPEDANCE:

72 ohms nominal

SPURIOUS SIGNALS:

All non-harmonic spurious frequencies above

60 cycles down at least 60 db.

INPUT POWER:

115/230 volts, 50 - 60 cps, single phase

SIZE:

All units of the Model CPS-1 require only 43-3/4

inches of standard 19 inch relay rack space.

WEIGHT:

Approx. 375 pounds.

COMPONENTS AND CONSTRUCTION:

All equipment is manufactured in accordance with JAN/MIL Specifications wherever practicable.

THE TECHNICAL MATERIEL CORPORATION

700 FENIMORE ROAD

MAMARONECK, NEW YORK

CABLE TEPEI MAMARONECK, N.Y. IN CANADA: TMC (CANADA) LTD. OTTAWA, ONTARIO